STZW402 | KI[™] Z-WAVE ELECTRONIC THERMOSTAT FOR SMART HOME





CONNECTED COMFORT

KI Z-Wave thermostats can easily be integrated into your home's Z-Wave network, so you can adjust the temperature setpoint of rooms in your home from a distance.



INTEGRATES EASILY WITH A SMART HOME HUB

CONTROL WITH A MOBILE APPLICATION DEPENDING ON THE HUB

| (v) |
|-----|
| |
| |

ELECTRICITY SAVINGS ENERGY SAVINGS OF 10-15% DEPENDING ON USE*

COMPATIBILITY

- · Z-Wave hub required
- Z-Wave Plus certified

COLOUR

• white

FINISH

molded plastic

WATTAGE AND VOLTAGE

- 150 W to 2000 W @ 120 V
- 300 W to 4000 W @ 240 V

CONTROL

- · two functions available: comfort and economy
- two- or four-wire connection
- outdoor temperature display[†]
- frost-free warning
- · display in Celsius or Fahrenheit
- backlit screen with adjustable intensity

ACCURACY

- accurate ambient temperature control of ± 0.5 °C (1 °F)
- CSA C828-13
- · temperature sensing with thermistor

TEMPERATURE RANGE

5 to 30 °C (41 to 86 °F)

WARRANTY

- three years
- * independent study
- † depending on the central controller and its application

COMPATIBLE WITH



For home automated system compatibilities and instructions on connecting to your KI thermostat, visit

www.stelpro.com. **TECHNICAL SPECIFICATIONS** PRODUCT FREQUENCY PACKAGING UNIT PRICE WATTS VOLTAGE AMPERAGE CODE MINIMUM MAXIMUM VOLTS AMPERES ΗZ STZW402WB+ 150/300 2000/4000 120/240 16.7 50/60 BOX

Dimensions: 4 7/8 in. (124 mm) wide, 4 7/8 in. (124 mm) high and 1 3/8 in. (29 mm) deep

Stelpro reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-colour products For all the latest models and prices, please refer to our website at www.stelpro.com.

99.00



Stelpro reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-colour products. For all the latest models and prices, please refer to our website at www.stelpro.com.