
Z-Wave Outdoor Plug - 2 Outlet



If you have any questions, please contact us at

Winnie@nie-tech www.nie-tech.com

Adding Device To Z-Wave Network for QR CODE



Scan here for SmartStar inclusion Note: DSK Code can be found on the packaging box. Do not remove or damage them.

Z-Wave Network Configuration

Add Device To Z-Wave Network

1. Follow the instructions for your Z-Wave certified controller to add a device to the Z-Wave network 2. Once the controller is ready to add your device, press the Manual/ Program button on the smart plug 3 times quickly. The blue LED will blink quickly. Auto-add mode: LED will blink within 30 seconds after first plugged in. Now, you have completed control to turn your fixture ON/OFF according to groups, schedules and interactive automation programmed by your controller. If your Z-Wave certified controller features remote access, you can control your fixture from your mobile devices.

To Remove The Device:

2. Once the controller is ready to remove your device, press the manual/program button on the smart plug 3 times quickly.

Factory Default:

Manual: Click the button twice quickly then hold for at least 10 seconds. (Light flashes once when reset successfully) Host reset: Remove it from hub the device will be restore to factory default

FCC warning:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference,

(2) This device must accept any interference received, including interference that may cause undesired operation, changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTF:

to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful

2. Read and follow all instructions that are on the product or provided with the product. interference in a residential installation. This equipment generates, uses and can radiate radio frequency 3. do not use an extension cord. energy and, if not installed and used in accordance with the instructions, may cause harmful interference 4. Reference the National Electrical Code, NFPA 70, specifically for the installation of wiring and clearances to radio communications. However, there is no guarantee that interference will not occur in a particular from power and lighting conductors. installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- -Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is receiver is
- Consult the dealer or an experienced radio/TV technician for help.

FCC Radiation Exposure Statement:

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled enviror This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter. This equipment should be installed and operated with minimum distance 20cm between the radiator &

CAUTION - PLEASE READ!

This device is intended for installation in accordance with the National Electric Code and local regulations SAVE THESE INSTRUCTIONS - This manual contains important safety and operating instrin the United States, or the Canadian Electrical Code and local regulations in Canada. If you are unsure

ortable about performing this installation consult a qualified electrician

MEDICAL EQUIPMENT

Please DO NOT use this plug to control Medical or Life Support equipment. This device should never be used to control the On/Off status of Medical and/or Life Support equipment.

OTHER WARNINGS

Risk of Fire / Risk of Flectrical Shock / Risk of Burns

IMPORTANT SAFETY INSTRUCTIONS

1. READ AND FOLLOW ALL SAFETY INSTRUCTIONS

5. Installation work and electrical wiring must be done by qualified person(s) in accordance with allapplicable codes and standards, including fire-rated construction.

6. do not install or use within 10 feet of a pool

7. do not use in a bathroom

8. WARNING:

Risk of Electric Shock

When used outdoors, install only to a covered Class A GFCI protected receptacle that is weatherpro with the power unit connected to the receptacle. If one is not provided, contact a qualified electrician for proper installation. Ensure that the power unit andcord do not interfere with completely closing the rece-

9. WARNING:

Risk of Electric Shock. Mount the unit at a height greater than 1 foot from the ground surface

10.WARNING:

tric fire. install only to a receptacle protected by 20A branch circuit over current protection.